

PVC Schedule 40 DWV Pipe

PVC Schedule 40 DWV Pipe



PVC SCHEDULE 40 (WHITE)		PLAIN END		PVC 1120	ASTM D 2665	
PART NO.	NOM. SIZE	UPC # 611942-	QTY. PER SKID	AVG. OD (IN.)	MIN. WALL (IN.)	WT. PER 100 FT. (LBS.)
PVC 7100*	1 1/4" x 10'	03945	2120'	1.660	.140	42.4
PVC 7100*	1 1/4" x 20'	03946	4240'	1.660	.140	42.4
PVC 7112*	1 1/2" x 10'	03947	1720'	1.900	.145	50.7
PVC 7112*	1 1/2" x 20'	03948	3440'	1.900	.145	50.7
PVC 7200*	2" x 10'	03949	990'	2.375	.154	68.1
PVC 7200*	2" x 20'	03950	1980'	2.375	.154	68.1
PVC 7300*	3" x 10'	03951	1040'	3.500	.216	141.2
PVC 7300*	3" x 20'	03952	920'	3.500	.216	141.2
PVC 7400†	4" x 10'	03953	600'	4.500	.237	201.2
PVC 7400†	4" x 20'	03954	1200'	4.500	.237	201.2
PVC 7500†	5" x 20'	04837	760'	5.563	.258	272.5
PVC 7600†	6" x 10'	03955	280'	6.625	.280	353.7
PVC 7600†	6" x 20'	03956	560'	6.625	.280	353.7
PVC 7800†	8" x 20'	03958	360'	8.625	.322	532.3
PVC 7910†	10" x 20'	03959	220'	10.750	.365	754.7
PVC 7912†	12" x 20'	03961	120'	12.750	.406	997.9
PVC 7914†	14" x 20'	04862	60'	14.000	.437	1180.1
PVC 7916†	16" x 20'	04918	60'	16.000	.500	1543.1

* Dual Marked ASTM D 1785 & ASTM D 2665.

† Triple Marked ASTM D 1785 & ASTM D 2665 & ASTM F 480.


NSF Listed. Meets All Requirements of
 ASTM D 1784, ASTM D 1785, and
 ASTM D 2665.



! WARNING

Testing with or use of compressed air or gas in PVC / ABS / CPVC pipe or fittings can result in explosive failures and cause severe injury or death.

AIR/GAS



- NEVER test with or transport/store compressed air or gas in PVC / ABS / CPVC pipe or fittings.
- NEVER test PVC / ABS / CPVC pipe or fittings with compressed air or gas, or air over water boosters.
- ONLY use PVC / ABS / CPVC pipe for water or approved chemicals.
- Refer to warnings in PFFA User Bulletin 4-80 and ASTM D 1785.