Clamp








Tube OD	Service Pressure Rating @ 70°F *	Service Pressure Rating @ 250°F *	А	304 Stainless Steel Part Number
1" - 1½"	100	75	2.080	13WGC100-150
2"	100	75	2.610	13WGC200
21/2"	100	75	3.140	13WGC250
3"	100	75	3.670	13WGC300
4"	100	75	4.780	13WGC400

^{*} finger tight

Spring Loaded Nut - 13SLN



- Lines using PTFE gaskets that are subject to large temperature swings can benefit from this special product. As the PTFE is compressed through the cycling of the lines, the spring load will help keep the connection from leaking.
 If the lines suffer from vibration and bolted clamps are not an option, refitting single pin
- If the lines suffer from vibration and bolted clamps are not an option, refitting single pin clamps with this nut will keep the connections from leaking for a longer time than the standard wing nuts.
- If you transport material in tanks via truck, the vibrations can loosen the standard single pin clamps. Spring loaded nuts can add a level of insurance to the shipment.
- Note: can be used on all wing nut style clamps



Thread	А	В	304 Stainless Steel Part Number
5/16 - 18	1.73	.875	13SLN

^{*} torque to 50 in. lb.

Torque-Rite® Nuts - 13TR

- an audible "click" indicating correct inch/pounds force
- maintains constant 30 or 50 inch/pounds force
- manual override feature
- retrofits all sanitary clamps, ¾" through 12"
- works in rupture disk applications
- no torque wrench or special training required

Description	Part Number
Torque-Rite® 30 in. lb nut	13TR-30
Torque-Rite® 50 in. lb nut	13TR-50



Accessories

Description		Part Number
	Cross hole wing nut 5/16"-18	13WNX
	Mini cross hole wing nut 5/16"-18 for ½" - ¾" clamps	13WNXM
	Serrated wing nut 5/16"-18	13WNS
	Hex wing nut 5/16"-18	13WNH
	Bronze hex nut 3/8"-16 for bolted clamps	13BN
ועו	Brass 3/8-16 nuts used on 10" & 12" bolted clamps	13BHN
U	Stainless steel hex nut for bolted clamps	13SN
	Bolt 3/8"-16 x 21/4" for 11/2" bolted clamps	13CB-2.25
	Bolt 3/8"-16 x 23/4" for 2" and 21/2" bolted clamps	13CB-2.75
	Bolt 3/8"-16 x 31/4" for 3" - 12" bolted clamps	13CB-3.25
	Rivet pin for ½" - 5" single pin clamps 5/16" x 1"	13RP
	Rivet pin for 6" and 8" single pin clamps 5/16" x 1-1/8"	13RP6
	5/16"-18 x 2" threaded eye bolt for ½" - 5" clamps	13IB
	5/16"-18 x 21/2" threaded eye bolt for 6" - 12" clamps	13IB6