

Product								
Fireplace Stub-Out (Male - NPT) for Use with TracPipe and CounterStrike								
Project Information								
Job Name:			Date Submitted:					
Location:			Submitted By:					
Engineer:			Approved By:					
Contractor:			Manufacturer's Rep:					
Installation								
Must be installed in accordance with the TracPipe Design Guide and Installation Instructions and all applicable codes								
Application Information								
Mounting plate with NPT B.I.P. Nipple. Angled to match the fireplace cabinet penetration requirements.								
Technical Data								
<u>Materials</u>								
Schedule 40 B.I.P.								
Mountaing Plate 12 ga. Carbon Steel								
<u>Pressure Ratings (used with tubing)</u>								
Specification Operating Pressure			25 PSIG					
CSA International Evaluation Report - Max Operating Pressure, 3/8" through 1-1/4"			125 PSIG					
<u>Temperature Ratings (used with tubing)</u>								
Operating Temperature Range			-20 to 200 Deg F					
Codes								
Standards								
NPT Threads per ANSI B1.20.1								
Listings								
Dimensional Information								
✓			<i>Flange Mount Dim (Nom)</i>	<i>Fitting length (Nom. in.)</i>	<i>TracPipe or CounterStrike Size</i>	<i>Weight (lbs)</i>		
☐	Size	P/N	5" x 5"	5-1/2"	1/2"	0.72		
	1/2"	FGP-FPT-500						

Omega Flex, Inc. * 451 Creamery Way*Exton, PA 19341

Tel: 610-524-7272 * Toll Free: 800-671-8622 * Fax: 610-524-7282

www.omegaflex.com